## **EUROPEAN PATENT OFFICE**

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

57177927

**PUBLICATION DATE** 

01-11-82

APPLICATION DATE

27-04-81

**APPLICATION NUMBER** 

56063639

APPLICANT:

NISSHIN STEEL CO LTD;

**INVENTOR:** 

IMATOMI HISAO;

INT.CL.

C21D 9/46 C21D 8/02 // C22C 38/28

TITLE:

MANUFACTURE OF HIGH TENSILE STEEL PLATE WITH SUPERIOR WORKABILITY

ABSTRACT:

PURPOSE: To manufacture a high tensile steel plate with ≥50kg/mm² tensile strength and superior workability by hot rolling a steel contg. specified amounts of C, Si, Mn, Cr and Al by an ordinary method and box-annealing it at a temp. from the A₁ transformation point to the A₃ transformation point.

CONSTITUTION: A steel consisting of, by weight,  $0.02{\text{-}}0.15\%$  C,  $0.1{\text{-}}1.5\%$  Si,  $1.9{\text{-}}3\%$  Mn,  $0.2{\text{-}}1.3\%$  Cr,  $\leq 0.1\%$  Al and the balance Fe with inevitable impurities is forged and hot rolled by an ordinary method at  $\geq 850^{\circ}$ C finish temp. and  $\geq 500^{\circ}$ C coiling temp. The rolled steel is then box-annealed at a temp. from the  $A_1$  transformation point to the  $A_3$  transformation point to obtain a composite structure contg. ferrite and martensite. It is more effective to add  $0.01{\text{-}}0.1\%$  Nb and/or  $0.01{\text{-}}0.2\%$  Ti to said composition.

COPYRIGHT: (C)1982,JPO&Japio

BNGDOCIO- > ID 357+770274 A I